

AU60.1



Nimi: Seadmekarp
 Seadmekarp 12-13/24-26 mm plaatseinale
 System Ideal
Tüüp: AU60.1
EAN: 6418677334788

Kirjeldus: AU60.1 seadmekarbil on keeratav rõngas, mille abil on võimalik korrigeerida paigaldatava seadme asendit, kinnituskruidid paiknevad teineteisest 60 mm kaugusel. Roheline adapter-rõngas väljaspool annab võimaluse karbi paigalduseks nii ühekordsesse (12-13 mm)plaatseina ja ilma rõngata, kahekordsesse (24-26 mm) plaatseina. Karbil on kaks 20 mm toruläbiviiku, mis on komplekteeritud üleminekutega 16 mm torule, lisaks saab paigaldada külgedele 4 lisa läbiviiku ja põhja 2.

AU60.1 on testitud kasutamiseks tulekindlates vaheseintes (EI60). Tulekindluse tagab karpide paigaldus vastavalt juhendile.

Karbid on valmistatud halogeenivabast materjalist (IEC/61249-2-21) ja läbinud hõõgtraadi testi IEC/EN60670:2005 (850 °C).

Pakend: 80
Toode: tk.



Spetsifikatsioon

Mõõtmed

Torule	Ø16/20mm
Nimipinge	400 V
Töötemperatuur	-25 ... 60 °C
Heakskiit	SP SITAC 1002, SC0854-09
ETIM	
ETIM 7	EC002601 (EC002601)
ETIM 8	EC002601 (EC002601)
ETIM 8	
Mounting method	Flush mounted (plaster)
Shape	Round
Construction type	Device connection box (round/square)
Model	Single

AU60.1

Provided with revolving ring	yes
Connectable	yes
Equipped with	None
Diameter	71 mm
Length	101 mm
Width	78.5 mm
Depth	58 mm
Internal depth	54 mm
Suitable for wall/board thickness	12 ... 24 mm
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	yes
Housing feed-through by break-out opening	yes
Housing feed-through by seal membrane	no
Housing feed-through by nozzle	yes
Housing feed-through by step membrane	no
For tube diameter	16/20 mm
Pipe locking	yes
Pipe locking optional	no
Inlet from the rear	yes
Number of inlets	9
Number of included spouts	2
Material	Plastic
Halogen free	yes
Surface protection	Untreated
Colour	Blue
Degree of protection (IP)	IP3X
Cover model	Construction protective cover
Transparent cover	no
Cover attachment	Snapped on
Sealable	no
Circuit integrity	None
With screening	no
Air tight	no
Max. conductor cross section	2.5 mm ²
Clamp position fixed	no
Luminaire hook mounting	no
Nozzle	None

AU60.1

With nail lugs	yes
Special application	None