



AP10M

Nimi: **Harukarp**
Harukarp pinnapealne 104 x 104 mm, must

Tüüp: AP10M
EAN: 6438199008158

Kirjeldus: Harukarp AP10 (6 mm², 500 V, kaitseaste IP65) on integreeritud kummläbiviikudega (12 tk külgedel ja 2 tk põhjas) varustatud jäiga korpusega karp. Sobib kuni Ø 19 mm kaablitele. Kaabliava kohad läbistatakse näit. kooritud juhtmeotstega. Kaas avatakse kruvikeerajaga kaanes olevatest piludest ja kinnitatakse surudes. Karpi saab paigaldada tõmbetakistid AS9, AS9.1 ja AS9.3.

Pakend: 5/30
Toode: tk.



Mõõtmed

Mõõtmed 104 x 104 mm

Classification

Kaitseaste IP65

Nimipinge 500 V

Juhi ristlõiked 6 mm²

Värvid

Värv Must

Värvikood RAL9003

Töötemperatuur -25 ... 60 °C

ETIM

ETIM 7 EC002600 (EC002600)

ETIM 8 EC002600 (EC002600)

ETIM 8

Max. conductor cross section 6 mm²

Equipped with None

Shape Square

Mounting method Universal

Mounting in the soil no

Mounting under water no

For tube diameter Other

AP10M

Inlet from the rear	yes
Length	104 mm
Width	104 mm
Depth	48 mm
Tackable	no
Number of inlets	14
Type of housing feed-through	Seal membrane
Material	Plastic
Halogen free	yes
Surface protection	Untreated
Colour	Black
Degree of protection (IP)	IP65
Degree of protection (NEMA)	Other
Cover model	Blind cover
Transparent cover	no
Cover attachment	Snapped on
Castable	no
With casting compound	no
Sealable	no
Rated insulation voltage Ui	500 V
Circuit integrity	None
With screening	no
Weatherproof	yes
Operating temperature	-25 ... 60 °C
Explosion-tested version	no
For Ex-zone gas	None
For Ex-Zone dust	None