

# AP75

Nimi: **Harukarp**  
Harukarp pinnapealne 75 x 75 mm, valge


Tüüp: AP75

EAN: 6410016125200

Kirjeldus: Harukarp AP75 (2,5 mm<sup>2</sup>, 450 V, kaitseaste IP65 on integreeritud kummläbiviikudega (10 tk külgedel ja 3 tk põhjas) varustatud jäiga korpusega karp. Sobib kuni Ø 18 mm kaablitele. Kaas avatakse kruvikeerajaga kaanes olevatest piludest ja kinnitatakse surudes. Karpi on võimalik plommida. Paigaldustemperatuur -15...+60°C.

Pakend: 5/50

Toode: tk.



## Spetsifikatsioon

### Mõõtmed

Mõõtmed 75x75 mm

### Classification

Kaitseaste IP65

Nimipinge 450 V

Juhi ristlõiked 2.5 mm<sup>2</sup>

### Värvid

Värv Valge

Värvikood RAL9003

### ETIM

ETIM 7 EC002600 (EC002600)

ETIM 8 EC002600 (EC002600)

### ETIM 8

Max. conductor cross section 2.5 mm<sup>2</sup>

Equipped with None

Shape Square

Mounting method Universal

Mounting in the soil no

Mounting under water no

For tube diameter Other

Inlet from the rear yes

# AP75

Length	75 mm
Width	75 mm
Depth	38 mm
Tackable	no
Number of inlets	13
Type of housing feed-through	Seal membrane
Material	Plastic
Halogen free	yes
Surface protection	Untreated
Colour	White
Degree of protection (IP)	IP65
Degree of protection (NEMA)	Other
Cover model	Blind cover
Transparent cover	no
Cover attachment	Snapped on
Castable	no
With casting compound	no
Sealable	yes
Rated insulation voltage $U_i$	400 V
Circuit integrity	None
With screening	no
Weatherproof	yes
Operating temperature	-15 ... 60 °C
Explosion-tested version	no
For Ex-zone gas	None
For Ex-Zone dust	None